

Overview

Product information

**DC50-01A(H)-11020000233**

Screw type Din-Rail TB, connector method: Screw/plug-in connector, Rated voltage: 1000 V, Rated current: 150 A, Number of connectors: 2, Number of potentials: 1, Cross section: 16 mm² - 50 mm², AWG: 6 - 1/0, Width: 20 mm, Color: gray, Mounting type: NS 35/7.5, NS 35/15

Product advantages

- ✓ Steel screw connection technology, reliable connection;
- ✓ Can be matched with marker strips to avoid incorrect insertion of wires.

Product certification

Technical data

Product drawing

3D model



Overview

Number of rows	1
number of connections	2
Open-end side panels	no
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0
Insulating material group	I
standard test	IEC60947-7-1
Connection method	screw connection

Dimension

width	20mm
End plate width	/
Height	75.85mm
NS 35/7,5 Height	75.9mm
NS 35/15 Height	83.4mm
length	70.45mm

Wiring data

Strip length	22~23mm
Conductor cross section solid AWG	6~1/0
Conductor cross section solid	16~50mm ²
Conductor cross section flexible	16~50mm ²
Conductor cross section flexible (ferrule without plastic sleeve)	16-50mm ²
Conductor cross section flexible (ferrule with plastic sleeve)	16-50mm ²
2 flexible conductors with a TWIN ferrule	10-16mm ²
Screw type	Allen screws
screw thread	M6
Tightening torque	2.5N.m

IEC Electrical parameters

Rated current(III/3)	150A
----------------------	------

IEC Electrical parameters

Rated voltage (III / 3)	1000V
Rated surge voltage	8KV

UL Electrical parameters

Rated voltage	600V
---------------	------

Rated current	125A
---------------	------

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Relative humidity (storage/transport)	25%~75%
Ambient temperature (storage / transport)	-25℃~60℃

Mechanical performance test

Mechanical strength	Passed the test
Fixing support	Passed the test
Rotational Pull Test	Passed the test

Electrical performance test

Voltage drop	≤3.2mV
Temperature rise test	≤45 K

Safety test

Anti-finger touch	Passed the test
-------------------	-----------------

Environmental protection

RoHS	No excessive harmful substances
REACH SVHC	Lead 7439-92-1

Accessories

Marker

Top marker	/
Side marker	ZT12
Marker support	/

Accessories

Slotted screwdriver size (Blade thickness x Width)	/
--	---

Bridge	FBI2-20 / FBI3-20
End cover	/
Partition plate	/

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2
DIN rail	NS35/7.5 & NS35/15

Business data

Order number	11020000233
Packing unit	10
Minimum order quantity	10
Products weight (without packaging)	115.767