


Overview

Product information



DHV6-PE-11010001085

Screw type rail terminal, connection method: screw connection, connection quantity: 2, number of digits: 1, wiring capacity: 0.2~10mm², AWG: 24~8, width: 7.5mm, color: yellow green, installation method: NS35/7.5, NS35/15

Product advantages

- ☒ Rated voltage in kilovolts
- ☒ Screw self-locking technology, superior anti loosening performance
- ☒ Copper alloy material with excellent conductivity
- ☒ 45 ° large area marking, easy to identify marking area

Product certification

Technical data

Product drawing

3D model

□

Overview

Number of rows	1
number of connections	2
Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0
Insulating material group	I
standard test	IEC60947-7-2
Connection method	screw connection

Dimension

width	8.2mm
End plate width	1.5mm
Height	51.5mm
NS 35/7,5 Height	59mm
NS 35/15 Height	66.5mm

Wiring data

Strip length	9~10mm
Conductor cross section solid AWG	24~10
Conductor cross section solid	0.2~6mm ²
Conductor cross section flexible	0.2~6mm ²

IEC Electrical parameters

Rated surge voltage	8KV
---------------------	-----

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Relative humidity (storage/transport)	25%~75%
Ambient temperature (storage / transport)	-25°C~60°C

Mechanical performance test

Mechanical strength	Passed the test
Fixing support	Passed the test
Rotational Pull Test	Passed the test

Electrical performance test

Voltage drop	≤3.2mV
Temperature rise test	≤45 K

Safety test

Anti-finger touch	Passed the test
-------------------	-----------------

Environmental protection

RoHS

No excessive harmful substances

REACH SVHC

Lead 7439-92-1

Accessories

Marker

Top marker bar

ZB8

Side marking strip

ZS8

Accessories

A screwdriver

0.8x4.0

Bridge components

DFBSXX-8.2(XX: 2-10,20)

End plate

D-DHV6

Grouping partition

ATP-DS / ATP-PC N

Installation

Terminal fixing components

E-PC 1100A / E-WS N

Terminal strip marking bracket

DLM2 / KLM3-20x8 / KLM3-44x8

DIN rail

NS35/7.5-1000-00A(H)

Guide rail protection cover

AP3-COVER / AP3-T / AP3-T-KS

Business data

Order number

11010001085

Packing unit

50

Minimum order quantity

50

Products weight (without packaging)

21.48

